

HEMA CANFL | INLINE VOLUMETRIC FILLER



HEMA CANFL Basics

- Designed for pasty & thick products
- 1,800 to 24,000 containers per hour
- Filling volume from 100 to 2,000 ml with 1 or 2 filling heads
- Metal, glass or plastic cans
- Ideal for corned beef, luncheon meat, goulash, tushunka, meat & fish pate, raw meat, pet food...
- Can be paired with a HEMA CS vacuum seamer for shaped or round cans.

HEMA CANFL Strengths

- Engineered for Performance
- High accuracy dosing
- Maintains product integrity
- Unmatched robustness & accessibility
- Production flexibility

BW Packaging Systems represents the collective capabilities of Barry-Wehmiller packaging companies including, BW Flexible Systems, BW Integrated Systems, BW Filling & Closing. Through their diverse capabilities, these companies can collectively provide everything from a single piece of equipment to fully integrated packaging systems for a wide range of industries, including: food and beverage, personal care, container manufacturing, pharmaceutical and medical devices, household products, paper products and textiles, industrial and automotive, and converting, printing and publishing. For more information, go to *BWPackagingSystems.com*



HEMA CANFL | COMPACT INLINE VOLUMETRIC FILLER



















Engineered for Performance

- Speed up to 400 cans per minute
- Different formats : round, rectangular or trapezoidal, with or without slope
- Running different materials : metal, glass or plastic
- Simplified mechanical design for vertical startup

High Accuracy Dosing & Integrity of your products

- Filling cornet with ball and circular cutting knife for hard pate or pieces
- Rotary knife for a perfect product cutting in case of meat with nerves as an alternative (round cans only)
- The "no can-no fill" concept limits losses and guarantees machine cleanliness
- The design of our filling valve guarantees optimal filling accuracy

Unmatched robustness & accessibility

- The entire mechanical part of the machine in the oil tank requires no lubrication (guaranteeing long equipment life)
- Safety guards with sliding doors (single head version) for easy access and cleaning, in compliance with EC standards
- A walkway gives access to the product feeding hopper for maintenance or cleaning
- Conveyor transfer: lifting platform in case of bottom filling system

Production flexibility

- Easy to use filler that requires minimal adjustments to set up
- Adjustment to the height of the frame and the filling volume is motorised.
- Production is managed from a tactile operating panel and different parameters are pre-programmed, depending on the recipes being filled.



